

EVGA SuperNOVA 850 G5, 80 Plus Gold 850W, Fully Modular, E-FDB Fan, 10 Year Warranty, Includes Power ON Self Tester, Com Size, Power Supply 220-G5-0850-X1

Part Num



The EVGA SuperNOVA G5 joins the elite ranks of the EVGA 80 PLUS Gold power supplies the award-winning G3 series, the G5 power supplies continue to push the envelope with the and Intel power-on standards. Starting with 80 PLUS Gold certification, a fully-modular cable Japanese capacitors, and an ultra-quiet 135mm Fluid Dynamic bearing fan with EVGA ECO supplies are built for performance and silence.

FEATURES

- 80 PLUS Gold certified, with 91% (115VAC) / 92% (220VAC~240VAC) efficiency or higher under typical loads
- 100% Japanese Capacitors ensure long-term reliability
- . Fully Modular to reduce clutter and improve airflow
- Fluid Dynamic Bearing Fan for ultra-quiet operation and increased lifespan.
- Unbeatable EVGA 10 Year Warranty and unparalleled EVGA Customer Support
- Active Clamp +DC to DC design for efficient operation
- · DC-DC Converter improves 3.3V/5V stability
- · Active Power Factor Correction
- EVGA ECO Intelligent Thermal Control System eliminates fan noise at low to medium loads
- · NVIDIA SLI & AMD Crossfire Ready
- Heavy-duty protections, including OVP (Over Voltage Protection), UVP (Under Voltage Protection), OCP (Over Current Protection), C Protection), SCP (Short Circuit Protection), and OTP (Over Temperature Protection)

CABLE LENGTH

| ATX Cable | 1x 600mm (m) | | |
|---------------------------|-----------------------------------|--|--|
| EPS Cable | 2x 700mm (m) | | |
| PCIe Cable | 2x 700mm, 2x 700mm, 850mm (m) | | |
| SATA Cable | 3x 550mm, 650mm, 750mm (m) | | |
| Four-Pin Peripheral Cable | 1x 550mm, 650mm, 750mm, 850mm (m) | | |
| Floppy Adapter | 1x 100mm | | |
| AC Power | 1x 1500mm (m) | | |
| Modular Cable Type | Full | | |

CONNECTOR QUANTITY

| 24 Pin ATX | 1x 24pin (20+4) |
|---------------------|-----------------|
| EPS (CPU) | 2x 8pin (4+4) |
| PCle | 6x 8pin (6+2) |
| SATA | 9x |
| Four-Pin Peripheral | 4x |
| Floppy | 1x |

INPUT

| Input Voltage | 100 - 240 VAC |
|-----------------------|--|
| AC Input | 12-5A |
| Input Frequency Range | 50/60 Hz |
| Efficiency | 91% (115VAC) / 92% (220VAC~240VAC) or Higher Typical |

OUTPUT

| Rail | +3.3V | +5V | +12V | -12V | |
|------------|-------------|-----|--------|------|---|
| Max output | 24A | 24A | 70.8A | 0.5A | |
| | | | 849.2W | | i |
| | 120W | | 849.2W | 6W | |
| Total | 850W @ +50C | | | | |

ADDITIONAL DETAILS

| Operating Temperature | 0° to 50° C | | |
|-----------------------|---|--|--|
| Japanese Capacitors | 100% | | |
| ECO Mode | Yes | | |
| MTBF | 100,000 Hours | | |
| Net Weight | 7 lbs | | |
| Size | 86mm (H) x 150mm (W) x 150mm (L) | | |
| Approvals | TUV, CB, CE, FCC, RCM, cTUVus, WEEE, RoHS Compliance with ErP Lot 3 2014 Requirement | | |
| Fan Size / Bearing | 135mm Fluid Dynamic Bearing | | |
| UPC | 843368062163 | | |
| EAN | 4250812433374 | | |



PRODUCT WARRANTY

This product is covered under EVGA's 10 year limited warranty which covers parts and labor. Further warranty extension is available upon registration within 90 days of purchase. For more details please visit http://www.evga.com/warranty/