ENHANCED FOR EFFICIENCY



FEATURES

3rd Generation Dual Chamber Pump – Newly designed dual chamber pump for improved overall cooling efficiency and performance.

Enlarged Cooling Surface Area – Increased surface area on the radiator for better heat dissipation and enhanced cooling performance

New SickleFlow 120 ARGB Fan – Improved lighting and performance using Air Balance fan blades, with new refreshed exterior design.

Reinforced Sealing – For improved longevity and Anti-Leaking Prevention

Addressable RGB Lighting Solution – Fully customizable addressable RGB lighting that is certified compatible with all major motherboard manufacturers' (Wired Controller also included).

PACKING INFORMATION

EAN code	4719512097625
UPC code	884102069925
Net weight	1.34 kg
Gross weight	1.98 kg
Carton dimension (L x W x H)	585 x 345 x 270 mm

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20′	1728	48	N/A
40′	3648	48	N/A
40 HQ	4104	54	N/A

The Perfect Start

CoolerMaster MasterLiquid ML240L ARGB V2 is a refreshed design from the popular MasterLiquid Lite Series that elevates the exterior design elements. The Pump of the ML240L ARGB V2 has been enhanced with the newly designed 3rd Gen. Dual Chamber Pump that improves the overall cooling efficiency of the AIO water cooler. The radiator surface area has been enlarged to increase the surface area for heat dissipation for optimized cooling performance. The ML240L ARGB V2 will included the latest SickleFlow 120 ARGB fan with a brand new design and Air Balance fan blades that is quieter than before without compromising on air flow and pressure.


SPECIFICATIONS

Product Name		MasterLiquid ML240L ARGB V2	
Product Num	ber	MLW-D24M-A18PA-R2	
Exterior Colo	r	Black	
CPU Socket	Intel	LGA 2066/ 2011-v3 / 2011 / 1151 / 1150 / 1155 / 1156 / 1200	
CPO Socket	AMD	AM4 / AM3+ / AM3 / AM2+/ AM2 / FM2+ / FM2 / FM1	
Radiator	Material	Aluminum	
Radiator	Dimensions (L x W x H)	277 x 119.6 x 27.2mm(10.9 x 4.7 x 1.1 inch)	
	Dimensions (L x W x H)	79.9 x 76 x 47.1mm(3.1 x 3 x 1.9 inch)	
	MTTF (Hours)	70,000 hours	
Rumn	Noise Level (dBA)	<15dBA	
Pump	Connector	3-Pin	
	Rated Voltage (VDC)	12	
	Power Consumption (W)	2.36 W (LED 2.21W)	
	Dimensions (L x W x H)	120 x 120 x 25mm (4.7 x 4.7 x 1 inch)	
	Quantity (pcs)	2	
	LED Type	ARGB	
	Speed (RPM)	650~1800RPM±10%	
	Airflow (CFM)	62 CFM (Max)	
Fan	Noise Level (dBA)	8~27 dBA	
	Pressure (mmH2O)	2.5 mmH ₂ O (Max)	
	Life Expectancy (Hours)	160,000 hours	
	Power Connector	4-Pin	
	Rated Voltage (VDC)	12	
	Rated Current (A)	0.15A (LED 0.2A)	
TDP (W)		200 W	
		N/A	
Warranty		2 years	



FEATURES







New Dual Chamber Pump

3rd Generation dual chamber pump designed for better performance and overall efficiency.

Larger Surface Area

Increased surface area of the fins on the radiator for better heat dissipation.

ARGB Ready

Refresh of the Masterliquid Lite comes in Addressable RGB allowing you to control the color mood of you build. Certified compatible with all major motherboard manufacturers.



Wired Controller Included

Perfect starter kit for those whom do not have RGB ports



Reinforced Sealing

Improved manufacturing process which will increase the lifespan of your cooler and also prevent leaking.



SickleFlow 120 ARGB

New SickleFlow 120 ARGB with improved performance and new exterior outlook