



J3060NH 6.X

- On board Intel Celeron J3060 Dual-core turbo boost up to 2.48G
- Supports 2 SO-DIMM of DDR3L 1600/1066MHz up to 16G maximum capacity
- Intel HD Graphics
- Mini ITX (17*17cm) for flexible use
- Support HDMI multimedia port
- Supports BIO-Remote 2 Technology
- Supports Charger Booster Technology

Chipset	<ul style="list-style-type: none"> • Braswell
CPU	<ul style="list-style-type: none"> • Intel® Celeron J3060 Dual-core turbo boost up to 2.48G
MEMORY	<ul style="list-style-type: none"> • Support Dual Channel DDR3L 1600/1066 MHz • 2 x DDR3 SO-DIMM Memory Slot • Max. Supports up to 8GB Memory for DDR3L-1600 OR 16GB Memory for DDR3L-1066 • ※The DIMM must be installed to DIMMA1 slot first.
INTEGRATED VIDEO	<ul style="list-style-type: none"> • Intel HD Graphics • Supports DX11.1 • Supports HDCP
STORAGE	<ul style="list-style-type: none"> • 2 x SATA III Connectors
LAN	<ul style="list-style-type: none"> • Realtek RTL8111H - 10/100/1000Mb/s Controller
AUDIO CODEC	<ul style="list-style-type: none"> • Realtek ALC662 6-Channel HD Audio
USB	<ul style="list-style-type: none"> • 2 x USB 3.0 Port • 1 x USB 3.0 Header • 2 x USB 2.0 Port • 2 x USB 2.0 Header
EXPANSION SLOT	<ul style="list-style-type: none"> • 1 x PCI-E 2.0 x1 Slot
REAR I/O	<ul style="list-style-type: none"> • 1 x PS/2 Mouse • 1 x PS/2 Keyboard • 2 x USB 3.0 Port

	<ul style="list-style-type: none"> • 2 x USB 2.0 Port • 1 x HDMI Connector • 1 x VGA Port • 1 x LAN Port • 3 x Audio Jacks
INTERNAL I/O	<ul style="list-style-type: none"> • 1 x USB 3.0 Header • 2 x USB 2.0 Header • 2 x SATA III Connector (6Gb/s) • 1 x Front Audio Header • 1 x Front Panel Header • 2 x System Fan Connector • 1 x COM Port Header • 1 x Printer Port Header
DIMENSION	<ul style="list-style-type: none"> • Mini ITX Form Factor Dimension: 17 cm x 17 cm (W x L)
OS SUPPORT	<ul style="list-style-type: none"> • Support Windows 7(x64) / 8.1(x64) / 10
ACCESSORIES	<ul style="list-style-type: none"> • 2 x SATA Cable • 1 x I/O Shield • 1 x DVD Driver • 1 x Quick Guide